

To be used in suites without gas appliances.



Now with Smart Hush™!

Hardwire Smoke Alarm with Smart Hush™

A working smoke alarm doubles a person's chance of surviving a fire. It can reduce fatalities up to 90%.

Features:



• **Ionization Technology** – Better at detecting fast flaming fires.



• **120V AC Direct-Wire** – Interconnects with up to 24 units, of which 18 can be initiating.



• **Test Button** – Tests circuitry and verifies alarm operation.



• **Smart Hush™ Button** – Quickly silences nuisance alarms and will not allow hush mode to be activated unless unit is in alarm mode.

• **Interconnectable** – ANY unit that senses a problem automatically triggers ALL units throughout the home immediately, allowing extra time for escape.

• **Quick Connect** – Installs quickly with snap-on wire harness.

Specifications:


Product dimensions:	6" x 6" x 1.5" deep
Colour / Case Pack:	White / 6 units
Electrical Rating:	120V AC, 60Hz, 60mA max per alarm
Wiring:	Quick connect plug with 8" pigtails
Audio Alarm:	85dB
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)
Humidity Range:	Up to 85% relative humidity
Sensor:	Ionization
Limited Warranty:	5 Year
Weight:	0.40lb
UPC:	0-47871-40379-0



P1235CA



Ionization
Ionisation



120 V



Test
Vérification



HUSH®



To be used in suites with gas appliances.



Hardwire Smoke & Carbon Monoxide Talking Alarm

Carbon monoxide is an invisible, odourless, poisonous gas that can be fatal when inhaled. It is the #1 cause of unintentional poisoning deaths in North America.

Features:



- **Ionization Technology** – Better at detecting fast flaming fires.
- **120V AC Direct-Wire** – Interconnects with up to 24 units, of which 18 can be initiating.
- **Test / Reset Button** – Tests circuitry and resets alarm.
- **Hush® Button** – Quickly silences nuisance alarms.
- **Talking Alarm** – Voice messages with sounding alarm identify different dangers.
- 2-in-1 unit – Advanced sensors for detecting both CO and smoke.

Specifications:

Product dimensions:	6" x 6" x 1.5" deep
Colour / Case Pack:	White / 6 units
Electrical Rating:	120V AC, 60Hz, 60mA max per alarm
Wiring:	Quick connect plug with 8" pigtails
Audio Alarm:	85dB
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)
Humidity Range:	Up to 85% relative humidity
Sensor:	Ionization and Electrochemical
Limited Warranty:	5 Year
Weight:	0.80lb
UPC:	0-47871-00133-0



900-0133

